

**WIDE PLANK
COLLECTION**
by Somerset™



NATURAL RED OAK
Red Oak

NATURAL WHITE OAK
White Oak

GUNSTOCK
Red Oak

COLONIAL GRAY
Red Oak

MIDNIGHT
Red Oak

MAPLE MIST
Maple

HICKORY TOAST
Hickory

HICKORY SADDLE
Hickory

ULTRA-WIDE PLANK FLOORING
IN OAK, MAPLE, AND HICKORY
MAKES A BIG DESIGN STATEMENT.



SOLIDPLUS™ ENGINEERED
1/2" thick, 3mm thick solid sawn wear
layer, 8-ply, random lengths up to 6-1/2'
WIDTHS: 6", 7"

WIDE PLANK: **SOLIDPLUS™** ENGINEERED



Product:	Somerset Wide Plank Collection Solid Plus Engineered Hardwood Flooring		
Species:	Hickory, Hard Maple, Red Oak, or White Oak (Somerset does not mix species.)		
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better.		
Dimensions:	Thickness: 1/2"*; 3mm* thick solid dry sawn wear layer Widths: 6", 7" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small>		
Construction:	8-ply cross-grain engineered construction; 7-ply birch core.		
Profile:	Eased Edge, Eased End		
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish		
Colors:	6" Width	7" Width	Wear Layer Species
	Natural Red Oak	EPWRON7E	Red Oak
	Natural White Oak	EPWWON7E	White Oak
	Gunstock	EPWGU7E	Red Oak
	Colonial Gray	EPWCG7E	Red Oak
	Midnight	EPWNN7E	Red Oak
	Maple Mist	EPWMM6E	Hard Maple
	Hickory Toast	EPWHTO6E	Hickory
	Hickory Saddle	EPWHTO6E	Hickory
Gloss Level:	Low Gloss		
Janka Hardness:	Species	Lbs	
	Red Oak	1290	Hickory 1820
	White Oak	1360	Hard Maple 1450
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request		
Flame Spread:	Class C; ASTM E84 Flame Spread Index - 138		
Formaldehyde Emissions:	ASTM D6007; BLQ (beneath limit of qualification - .008ppm)		
Critical Radiant Flux (CRF):	ASTME648 - Test in Progress		
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, revised: March, 2007.) Installation guidelines are printed on the bottom of each carton and available at www.somersetfloors.com		
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)		
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)		
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer		